

# ForceField® FloorBlaster Hard Surface Cleaner - Ready to Use

# SAFETY DATA SHEET

### SECTION 1 - CHEMICAL AND COMPANY IDENTIFICATION:

Product Name: FloorBlaster Hard Surface Cleaner – Ready to Use Date Printed: 10/4/2018

Product Use/Class: Hard Surface, Laminate, Flooring Cleaner Product ID: F HSC

Supplier: Shield Industries, Inc.

Address: 131 Smokehill Lane

Manufacturer: Shield Industries, Inc.

Address: 131 Smokehill Lane

Woodstock, GA 30188 - USA Woodstock, GA 30188 - USA

Telephone: 770-517-6869 24 Hour Emergency Hotline: 800-535-5053

# **SECTION 2 – HAZARD IDENTIFICATION:**

Physical hazards: Not applicable ------

**Health hazards:** Acute Toxicity Category 4

Skin sensitization Category 2
Eye sensitization Category 2
Specific target organ toxicity, Category 3

single exposure

**Environmental hazards:** No data available. **OSHA defined hazards:** Not classified.

**Label elements:** 

**(!**)

Signal word: Warning

**Hazard statement** Harmful if swallowed, inhaled, or in contact with skin. (H302 + H312 + H332)

Causes skin irritation. (H315) Causes serious eye irritation. (H319) May cause respiratory irritation. (H335)

**Precautionary statements:** 

**Prevention:** Wear protective gloves/protective clothing/eye protection/face

protection. (P280)

Wash hands and exposed skin thoroughly after handing. (P264)

ForceField® FloorBlaster Hard Surface Cleaner – Ready to Use

Avoid breathing dust/fume/gas/mist/vapours/spray. (P261)

Contaminated work clothing should not be allowed out of the workplace.

(P272)

**Response:** IF SWALLOWED: Get medical advice/attention. Do NOT Induce vomiting.

(P301 + P313 + P331)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+

P338)

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in

a position comfortable for breathing. (P304 + P341)

If experiencing respiratory symptoms: Call a POISON CENTER or

doctor/physician. (P342 + P311)

**Storage:** Keep out of reach of children. (P102)

**Disposal:** Dispose of contents/container to an approved waste disposal plant. (P501)

Hazard(s) not otherwise

**classified (HNOC):** None.

**Supplemental information:** None.

#### SECTION 3 COMPOSITION/INFORMATION ON COMPONENTS

<u>COMPONENTS</u>	<b>CAS NUMBER</b>	<u>%</u>
Water	7732-18-5	> 95 %
Proprietary ingredient(s)	Trade Secret*	<1 %
Surfactant(s)	Trade Secret*	< 1 %
2-(2-Butoxyethoxy) ethanol	112-34-5	< 1 %
Tetrasodium EDTA	64-2-8	< 0.1 %
Fragrance Compound	N/A (Mixture)	< 0.1 %
Proprietary preservative	Trade Secret*	0.1 - 0.5 %
Colorant	Trade Secret*	< 0.01 %

<sup>\*</sup> Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

# **Additional Information:**

Substances in the product which may present a health or environmental hazard, or which have been assigned occupational exposure limits, are detailed below:

Ethylene glycol n-butyl ether (CAS# 111-76-2)

#### SECTION 4 FIRST AID MEASURES

**Inhalation:** Move person to fresh air and keep at rest in a position comfortable for

breathing. If breathing is labored, administer oxygen. If systems persist, contact a

POISON CENTER or doctor/physician. If breathing stops, give artificial respiration.

**Skin contact:** If on skin, wash thoroughly with soap and water. If on clothes, remove clothing. Get

medical attention if irritation or rash develops and persists.

ForceField® FloorBlaster Hard Surface Cleaner – Ready to Use

**Eve contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Keep eyes wide open and continue rinsing. Get immediate medical

attention.

**Ingestion:** Keep respiratory tract clear. Do NOT induce vomiting. Aspiration hazard. Never

give anything by mouth to an unconscious person. If conscious, give 8 to 16 ounces of

water or milk to dilute substance. Seek medical attention immediately.

### Most important symptoms/effects, acute and delayed:

Eyes: Direct contact may cause irritation, including stinging, tearing, redness, and swelling.

Skin: Prolonged or repeated contact may cause irritation, itching, redness, or de-fatting,

leading to dryness. May be absorbed through the skin and cause effects similar to

inhalation exposure.

Inhalation: Organic solvent vapours or mists from this product may cause irritation of the nose

mouth, throat and lungs. Breathing large amount of organic solvent vapours or mists

may affect the central nervous system; causing headache, dizziness, nausea,

confusion,

loss of coordination, impaired judgment, or similar effects.

Ingestion: Ingestion causes irritation of the mouth, throat, and stomach. Swallowing large

amounts of organic solvents may affect the central nervous system, causing effects

similar to inhalation exposure.

### Indication of immediate medical attention and special treatment needed:

If ingested: Immediately seek medical attention. Provide general supportive measures and treat symptomatically.

If symptoms of inhalation exposure (noted above) are present: Immediately seek medical attention. Keep victim under observation. Symptoms may be delayed.

### **General information:**

Move affected persons from dangerous area. Do not leave victim unattended. Ensure that medical personnel are aware of the material(s) involved. Show this safety data sheet to the doctor in attendance.

#### SECTION 5 FIRE FIGHTING MEASURES

# Suitable extinguishing media:

Non-combustible. Use media appropriate for surrounding fire.

#### **Unsuitable extinguishing media:**

Do not use water jet.

# Specific hazards arising from the chemical:

Combustion or thermal decomposition will evolve toxic and/or irritant vapours.

Forms fumes of oxides of carbon, nitrogen, and sulfur.

# Special protective equipment and precautions for firefighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and self-contained breathing apparatus (SCBA).

# **Fire-fighting equipment/instructions:**

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up.

#### **Specific methods:**

Evacuate and keep any non-responders away. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area

ForceField® FloorBlaster Hard Surface Cleaner – Ready to Use

if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

#### General fire hazards:

None known.

#### SECTION 6 ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures:

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not get in eyes. Avoid skin contact. Do not breathe vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them.

# **Environmental precautions:**

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. Prevent further leakage or spillage if safe to do so. Inform appropriate managerial or supervisory personnel and authorities of all environmental releases.

# Methods and materials for containment and cleaning up:

Contain spillages and then collect with sand, earth, diatomaceous earth, vermiculite, or any other suitable adsorbent material. Collect spillage. Transfer to a container for disposal or recovery. Following product recovery, flush area with water. If possible prevent water running into sewers. For waste disposal, see section 13 of the SDS.

#### SECTION 7 HANDLING AND STORAGE

### **Precautions for safe handling:**

Avoid contact with skin and eyes. Wear appropriate personal protective equipment. Smoking, eating and drinking should be prohibited in the application area. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. Use product in a well-ventilated area only. Do not handle near an open flame, heat, sparks, or other source of ignition.

#### Advice on protection against fire and explosion:

None – Product is non-combustible

# Conditions for safe storage, including any incompatibilities:

Keep container tightly closed in a dry and well-ventilated place away from incompatible materials. Keep cool. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Avoid storing in the presence of oxidizing or reducing agents. Protect from sunlight. Do not store near an open flame, heat, sparks, or other source of ignition.

#### SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Occupational exposure limits:

#### **US. ACGIH Threshold Limit Values**

Components	CAS	Type	<u>Value</u>	
2-(2-Butoxyethoxy)	112-34-5	TWA(8 hr.)	$20 \text{ ppm } (97 \text{ mg/m}^3)$	
ethanol		Notation	Skin	
US. OSHA Limit Values				
Components	CAS	Type	<u>Value</u>	
2-(2-Butoxyethoxy)	112-34-5	TWA(8 hr.)	50 ppm (240 mg/m <sup>3</sup> )	

# **Appropriate engineering controls:**

ethanol

Provide sufficient mechanical ventilation (general and local exhaust) to maintain exposure below the level of overexposure from known, or apparent, adverse effects.

Notation

Skin

# Individual protection measures, such as personal protective equipment:

# **Eye/face protection:**

Wear safety glasses with side shields (or goggles). A splash shield is recommended when splashing is possible.

# Hand protection:

Wear appropriate chemical resistant gloves (Butyl rubber, Neoprene, or Natural rubber) to minimize skin contact. Check with protective equipment manufacturer's data.

#### **Skin protection/Other:**

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

# **Respiratory protection:**

Not normally required. If workplace permissible exposure limits of product, or any component, are exceeded: Use NIOSH approved air supplied respirator in the absence of proper environmental controls. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions. (Consult your safety representative.) controls, or administrative controls, should be implemented to reduce exposure.

### Thermal hazards:

Not normally required.

# General hygiene considerations:

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### **Environmental exposure controls:**

Do not allow to enter drains, sewers or waterways. Avoid release to the environment. Material is very toxic to aquatic life with long lasting effects.

# SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Physical state: Liquid
Form: Liquid
Color: Clear amber

**Odor:** Characteristic, Sweet Fruity

Odor threshold:Not available.pH:7.0 +/- 1.0Melting point/freezing point:Not available.Initial boiling point and boiling rangeNot determined.

Flash point: > 200 °F (Tag closed cup)
Evaporation rate: Approximately 1 (water = 1)

Flammability (solid, gas): Not applicable.

**Upper/lower flammability or explosive limits:** 

Flammability limit – lower (%): 0.85% (v) (2-(2-Butoxyethoxy) ethanol)
Flammability limit – upper (%): 24.6% (v) (2-(2-Butoxyethoxy) ethanol)

Explosive limit - lower (%): Not available. Explosive limit - upper (%): Not available.

**Vapor pressure:** 0.06 mm Hg @ 68 °F (2-(2-Butoxyethoxy) ethanol)

Relative Vapor density:Heavier than air.Relative density:1.02 +/- 0.02Solubility (water):SolublePartition coefficient (n-octanol/water):Not available.

**Auto-ignition temperature:** 442 °F (2-(2-Butoxyethoxy) ethanol)

**Decomposition temperature:**Not available. **Viscosity (kinematic cSt @ 40 °C):**Not available.

**Other information:** None.

### SECTION 10 STABILITY AND REACTIVITY

#### Reactivity:

The product is stable and non-reactive under normal ambient conditions of use, storage and transport.

### Chemical stability:

Material is stable under normal conditions.

#### Possibility of hazardous reactions:

None anticipated.

#### Conditions to avoid:

Avoid contact with heat, ignition sources, and incompatible materials. Avoid concentrating by evaporation to dryness, as unstable peroxides may form.

#### **Incompatible materials:**

Strong oxidizing or reducing agents.

# **Hazardous decomposition products:**

At temperatures over 200 C, or under fire conditions, thermal decomposition will evolve toxic and irritant vapours. Forms: oxides of carbon, nitrogen, and sulfur.

#### SECTION 11 TOXICOLOGICAL INFORMATION

### **Information on likely routes of exposure:**

Inhalation: May cause mild irritation to respiratory tract.Skin contact: May cause skin irritation and/or dermatitis.Eye contact: Vapors may cause irritation to the eyes

#### Symptoms related to the physical, chemical and toxicological characteristics:

Eye irritation: Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation: May cause redness and/or degreasing of skin. May be absorbed through the skin

and cause effects similar to inhalation exposure.

Inhalation: Organic solvent vapours or mists from this product may cause irritation of the nose mouth, throat and lungs. Breathing large amount of organic solvent vapours or mists may affect the central nervous system; causing headache, dizziness, nausea,

confusion.

loss of coordination, impaired judgment, or similar effects.

Ingestion: Ingestion causes irritation of the mouth, throat, and stomach. Swallowing large amounts of organic solvents may affect the central nervous system, causing effects similar to inhalation exposure.

# Information on toxicological effects:

**Acute toxicity:** 

Components	CAS#	Test	Species	Test Results
2-(2-Butoxyethoxy)	112-34-5	Acute Oral LD50	Rat	5,080 mg/kg
ethanol		Acute Oral LD50	Mouse	2,406 mg/kg
		Acute Dermal LD50	Rabbit	2,467 mg/kg
Surfactant(s)		Acute Oral LD50 Acute Dermal LD50	Rat Rabbit	7,200 mg/kg > 2,000 mg/kg
Tetrasodium EDTA	8013-51-2	Acute Oral LD50	Rat	> 2,000 mg/kg

**Skin corrosion/irritation:** May cause skin irritation and/or dermatitis.

**Serious eye damage/eye irritation:** Causes serious eye irritation.

Respiratory or skin sensitization:

**Respiratory sensitization:** Vapours may cause irritation.

**Skin sensitization:** Not determined, however none of the components of this

mixture are known, or suspected, skin sensitizers.

**Germ cell mutagenicity:** No data available to indicate product or any

components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity: None of the ingredients in this product are considered

to be a carcinogen by IARC, ACGIH, NTP, or OSHA

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Not listed.

### Repeated dose toxicity:

Component: 2-(2-Butoxyethoxy) ethanol

Species: Rat

Application Route: Oral (Drinking water.)

NOAEL: 250 mg/kg/day

Test Duration: 90 days

Component: 2-(2-Butoxyethoxy) ethanol

Species: Rat Application Route: Dermal

NOAEL: > 2,000 mg/kg/day

Test Duration: 90 days

Component: 2-(2-Butoxyethoxy) ethanol

Species: Rat
Application Route: Inhalation
NOAEL: 0.094 mg/l
Test Duration: 90 days

# Specific target organ toxicity - single exposure:

This mixture has not been tested. However, trace levels of Ethylene glycol N-butyl ether may be present within the mixture. Studies in rats and rabbits suggest that Ethylene glycol N-butyl ether may have hemolytic effects on red blood cells that eventually lead to further effects on the liver and kidneys. Their relevance to human metabolic mechanisms, expected occupational doses, or likely routes of exposure is not clear or confirmed.

#### **Teratogenicity:**

No data available.

#### **Aspiration hazard:**

Components within this product may present an aspiration hazard, however no specific data is available.

### SECTION 12 ECOLOGICAL INFORMATION

**Ecotoxicity:** Very toxic to aquatic life with long lasting effects.

#### **Acute Toxicity:**

Components/CA	S Test	Species	Test Results
2-(2-Butoxyethox	y) Aquatic Fish LC50	Fish	1,300 mg/l, 96 hr.
ethanol/	Aquatic Crustacea EC50	Water flea (Daphnia magna)	100 mg/l, 48 hr.
112-34-5	Aquatic Plants EC50	Alga	100 mg/l, 96 hr.
Surfactant(s)/	Aquatic Fish LC50	Fish	>= 1,000 mg/l, 96 hr.
Trade secret	Aquatic Crustacea EC50	Water flea (Daphnia magna)	1,000 mg/l, 48 hr.
	Aquatic Plants EC50	Alga	>= 230 mg/kg, 72 hr.
Tetrasodium EDT	<b>A</b>	Bull gill sunfish	760 mg/l, 96 hr.
8013-51-2	Aquatic Fish LC50	Fathead minnow	59.8 mg/l, 96 hr.

# Long Term Toxicity:

No data available.

#### Persistence and degradability:

2-(2-Butoxyethoxy) ethanol: Readily biodegradable (85%/ 28 days)

# **Bioaccumulative potential:**

No data available.

#### Mobility in soil:

No data available.

#### Results of PBT and vPvB assessment:

No data available.

#### Other adverse effects:

None known.

#### SECTION 13 DISPOSAL CONSIDERATIONS

#### Waste treatment/disposal instructions:

Disposal should be in accordance with local, state, or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

# Waste from residues / unused products:

Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. Dispose of in accordance with local regulations.

### **Contaminated packaging:**

Exercise caution as empty containers or liners may retain some product residues. Do not reuse empty containers. Do not burn, or use a cutting torch on, empty containers. Empty containers should be taken to an approved waste handling site for recycling or disposal.

\_\_\_\_\_

#### SECTION 14 TRANSPORT INFORMATION

#### DOT

**UN number:** Not applicable

**UN proper shipping name:** Cleaning compounds N.O.S.

**Transport hazard class(es):** 

Class: Not applicable

Subsidiary risk: -

Label(s): Not applicable Packing group: Not applicable

Special precautions for user:

Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

**Environmental hazards:** No

**Special provisions:** None Assigned

**Packaging exceptions:** 

None – Not classified as dangerous for transportation

#### Packaging bulk:

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

#### **IATA**

**UN number:** Not applicable

**UN proper shipping name:** Cleaning compounds N.O.S.

Transport hazard class(es):

Class Not applicable

Subsidiary risk -

Label(s)Not applicablePacking groupNot applicable

**Environmental hazards** No

**ERG Code** Not applicable

**Special precautions for user:** 

Read safety instructions, SDS and emergency procedures before handling. Read Safety instructions, SDS and emergency procedures before handling.

# Packaging bulk:

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

#### **IMDG**

**UN number:** Not applicable

**UN proper shipping name:** Cleaning compounds, n.o.s.

Transport hazard class(es):

Class: Not applicable

**Subsidiary risk:** -

**Label(s):** Not applicable **Packing group:** Not applicable

**Environmental hazards: Marine pollutant:** No

**Special precautions for user:** 

Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

#### Packaging bulk:

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

#### **SECTION 15 REGULATORY INFORMATION**

#### **US federal regulations:**

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List or polymer exempt.

# **CERCLA Hazardous Substance List (40 CFR 302.4)**

Component: CAS# RQ 2-(2-Butoxyethoxy) ethanol 112-34-5 None

# SARA 311/312 – Superfund Amendments and Reauthorization Act of 1986:

# Hazard categories:

Immediate Hazard Yes
Delayed Hazard Yes
Fire Hazard No
Sudden Release No
Reactivity No

# **SARA 313 – Toxic Chemicals (40 CFR 372.38(a)):**

Certain glycol ethers category.

#### SARA 302/304 Threshold Planning Quantity:

Not regulated.

### Other federal regulations:

#### Clean Air Act (CAA) Ozone-Depletion Potential:

This product neither contains, nor was manufactured with a Class I, or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App. A+B).

### **US** state regulations

# **U.S. California Proposition 65:**

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive effects.

\_\_\_\_\_

#### SECTION 16 OTHER INFORMATION

NFPA RATING: HEALTH: 2 FLAMMABILITY: 1 REACTIVITY: 0

Personal protection rating to be supplied by user depending on use conditions.

PREPARATION INFORMATION:

DATE CREATED: 01/01/06 LAST REVISION: 9/27/2018

CREATED/REVISED BY: R. Lasnik

This information relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of this information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer warranty against patent infringement.

#### End of SDS