



ST-19

90 MIN FIRE ASSEMBLY- LIGHT WEIGHT STRUCTURAL STEEL BEAM

TYPICAL ASSEMBLY - LIGHT WEIGHT STRUCTURAL STEEL MEMBER USED HORIZONTALLY AS A
BEAM OR 45 DEG BRACING

Light weight defined as 1 LBS-9.9 LBS. per liner foot of material



TO ACHIEVE 90 MIN RATING (USING CRITERIA 1300 ° F AVERAGE):

PREPARATION OF STEEL MEMBER: CLEAN AND APPLY COMPATIBLE STEEL PRIMER @ 2.5 MIL.

APPLY 60 MIL THICKNESSES (DRY) OF ForceField® FireGuard® E-84 TO ALL EXPOSED SIDES OF STEEL BEAM.



60 MIL THICKNESS (DRY) OF FFG E-84
INTUMESCENT COATING

SCALE: N.T.S.

FIRE TEST ENDURANCE RATING:	90 MIN
STANDARD TESTED TO:	ASTM E-119-11A STRUCTUAL STEEL SECTION; NFPA 251; UL 263; ULC S-101-07 WITH NO LOAD CAPACITY, NO RESTRAINT, SMALL SCALE TEST
FIRE TESTED LABORATORY	GUARDIAN FIRE LABORATORIES, INC. 480 HINMAN AVE. BUFFALO, NY 14216
REPORT NO:	GL 115611
PRODUCT:	ForceField® FireGuard E-84® INTUMESCENT COATING (FFG E-84)
MANUFACTURER:	SHIELD INDUSTRIES, INC. 131 SMOKEHILL LANE WOODSTOCK, GA 30188
*SEE MANUFACTURER APPLICATION INSTRUCTIONS AND SPECIFICATIONS FOR SURFACE PREPARATION AND APPLICATION PROCESS	